



Modelling Uw-Value	0.11 W/m <sup>2</sup> K
Elemental Uw-Value	0.12 W/m <sup>2</sup> K
Modelling U <sub>F</sub> -Value	0.094 W/m <sup>2</sup> K
Elemental U <sub>F</sub> -Value	N/A
Psi Value	0.091 W/mK
fR <sub>si</sub> Value	0.92

## KORE Insulated Foundation System - Twin Framed Timber Frame Wall

**Disclaimer:**  
 The information in this document is to the best of our knowledge, true and accurate. However and recommendations or suggestions contained within are without guarantee and as the conditions of use are beyond our control. Recommendations for use should be verified for suitability and compliance with actual requirements specifications and any applicable laws and regulations. KORE technical literature and our Agreement certificates are all available for download from our website [www.kore-system.com](http://www.kore-system.com). Airpacks Ltd t/a KORE reserves the right to amend product specifications without prior notice. Please check that the copy of this literature is current by contacting the KORE marketing department.



**INSULATION AND ENERGY SAVING SOLUTIONS**  
[www.kore-system.com](http://www.kore-system.com)

Kilnaleck, Co. Cavan, Ireland Phone: +353 49 4374000 Fax: +353 49 4336823

Project : KORE Standard Details		
Title: KORE Foundation - Twin Framed Timber Wall		
Drawn: /	Checked: /	Date: 03/02/2020
Drawing N°: TF_06	Rev: A	
Scale: 1 : 10 @ A4	Drawn by Airpacks Ltd. t/a KORE	